

tesa® 50525 PV1

Conformable 30µm aluminium tape with liner

tesa® 50525 PV1 is a conformable aluminium tape, based on a 30µm aluminium foil and an acrylic adhesive.
tesa® 50525 PV1 is a very flexible tape mainly used in the appliance industry and also for a wide range of other applications.

Features:

- good adhesion
- conformable
- moisture resistant
- vapour tight
- high thermal conductivity
- ageing-resistant

Main Application

- Mounting of refrigeration coils
- General purpose temperature insulation
- Sealing of ducts
- Masking, protecting, repairing, closing ...and a lot more!

Technical Data

▪ Backing material	aluminium foil	▪ Tensile strength	23 N/cm
▪ Total thickness	60 µm	▪ Temperature resistance min.	-40 °C
▪ Type of adhesive	acrylic	▪ Temperature resistance max.	160 °C
▪ Adhesion to steel	5 N/cm	▪ Surface finish	reflective
▪ Elongation at break	5 %		

Properties

- | | | | |
|-----------------------|-----|--------------------|------|
| ▪ Abrasion resistance | ●●● | ▪ Water resistance | ●●●● |
|-----------------------|-----|--------------------|------|

Evaluation across relevant tesa® assortment: ●●●● very good ●●● good ●● medium ● low

For latest information on this product please visit <http://l.tesa.com/?ip=50525>

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.