

tesa® 51025 PV10

Handtearable PET cloth tape

tesa® 51025 PV10 is a PET cloth wire harness tape with a solvent-free rubber based adhesive.

Major Features:

- Temperature resistance 125°C/3000h
- Solvent-free adhesive
- Handtearable

Color: Available in black

Main Application

tesa® 51025 PV10 is designed for wrapping up to a temperature class of 125°C.

Technical Data

▪ Backing material	PET cloth	▪ Temperature resistance (3000h)	125 °C
▪ Total thickness	160 µm	▪ Abrasion resistance (10mm mandrel)	Class B (acc. to LV312)
▪ Type of adhesive	rubber based	▪ Abrasion resistance (5mm mandrel)	Class A (acc. to LV312)
▪ Adhesion to steel	6.5 N/cm	▪ Flame resistance as composite	Class B (acc. to LV312)
▪ Elongation at break	25 %	▪ Unwind force (roll width ≤ 9mm)	8 N/roll (30 m/min)
▪ Tensile strength	80 N/cm	▪ Unwind force (roll width > 9mm)	8 N/roll (30 m/min)
▪ Temperature resistance min.	-40 °C	▪ Noise damping (decibel)	Class A (acc. to LV312)

Additional Information

- Technical data acc. to LV 312

For latest information on this product please visit <http://l.tesa.com/?ip=51025>

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.