productinformation

tesa[®] 51606 PET fleece tape for high noise damping

tesa® 51606 is a thick PET fleece wire harness tape with a rubber based adhesive.

Major Features:

- High noise damping
- High abrasion resistance

Color: Available in black

Main Application

tesa® 51606 is designed for the passenger compartment, providing high noise damping.

Technical Data

	Backing material Total thickness Type of adhesive Adhesion to steel Elongation at break	PET fleece 800 μm rubber based 5.5 N/cm 85 %	•	Abrasion resistance (10mm mandrel) Abrasion resistance (5mm mandrel) Flame resistance as composite	Class D (acc. to LV312) Class C (acc. to LV312) Class B (acc. to
	Tensile strength	55 N/cm			LV312)
	Temperature resistance min.	-40 °C		Unwind force (roll width ≤ 9mm)	7.5 N/roll (30 m/min)
•	Temperature resistance (3000h)	105 °C	1	Unwind force (roll width > 9mm) Noise damping (decibel)	7.5 N/roll (30 m/min) Class D (acc. to

Additional Information

- Technical data acc. to LV 312
- Applicable for red ring assembly aid

For latest information on this product please visit http://l.tesa.com/?ip=51606

tesa[®] products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa[®] product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



LV312)

0.066 W/mK

Thermal conductivity x-y-direction