

tesa® 51619

PET fleece tape for flexibility and noise damping

tesa® 51619 is a PET fleece wire harness tape with a rubber based adhesive.

Major Features:

- Noise damping
- Abrasion resistant
- Handtearable

Color: Available in black

Main Application

tesa® 51619 is designed for the passenger compartment, providing flexibility and noise damping.

- Specifically made for automatic bundling

Technical Data

▪ Backing material	PET fleece	▪ Temperature resistance (3000h)	105 °C
▪ Total thickness	250 µm	▪ Abrasion resistance (10mm mandrel)	Class B (acc. to LV312)
▪ Type of adhesive	rubber based	▪ Abrasion resistance (5mm mandrel)	Class A (acc. to LV312)
▪ Adhesion to steel	3 N/cm	▪ Flame resistance as composite	Class B (acc. to LV312)
▪ Elongation at break	20 %	▪ Unwind force (roll width ≤ 9mm)	4 N/roll (30 m/min)
▪ Tensile strength	37 N/cm	▪ Unwind force (roll width > 9mm)	4 N/roll (30 m/min)
▪ Temperature resistance min.	-40 °C	▪ Noise damping (decibel)	Class C (acc. to LV312)

Additional Information

- Technical data acc. to LV 312

For latest information on this product please visit <http://l.tesa.com/?ip=51619>

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.