

tesa® EasySplice 61152 CoaterLine Premium Repulpable, double-sided splicing tape

tesa® 61152 EasySplice® CoaterLine Premium is a repulpable double-sided integrated flying splice tape consisting of a flat-back paper and a modified water soluble acrylic adhesive.

tesa® 61152 EasySplice® CoaterLine Premium features especially:

- Very high heat resistance
- Very high tack properties
- Very good adhesion values on coated and uncoated paper
- Low splice thickness
- Printable and coatable backing
- Good repulpability over full pH-range (pH3 –pH9)

Following functions are provided:

- Slit liner for the secure fixation of the top sheet
- Adhesive formulation with very high tack properties for excellent contact between expiring web and new reel
- Two white splitting strips with paper backing for a smooth opening of the new paper reel without jeopardizing the coating process and for a secure attachment of the tape to the paper roll – no folding back of tape while attaching top sheet

Colour: Blue

Main Application

tesa® 61152 EasySplice® CoaterLine Premium is particularly suitable for:

- Flying splice applications on off-line coaters with a splicing speed <900m/min and a coating width of <4m

Technical Data

▪ Backing material	flat paper	▪ Tensile strength	30 N/cm
▪ Total thickness	100 µm	▪ Type of liner	repulpable siliconised paper
▪ Type of adhesive	repulpable tackified acrylic	▪ Shelf life time (packed) < 25°C	12 months
▪ Elongation at break	6 %		

Properties

- | | | | |
|--------|------|---------------------------|-----|
| ▪ Tack | ●●●● | ▪ Static shear resistance | ●●● |
|--------|------|---------------------------|-----|

Evaluation across relevant tesa® assortment: ●●●● very good ●●● good ●● medium ● low

For latest information on this product please visit <http://l.tesa.com/?ip=61152>

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.