productinformation

tesa® 68618

150µm double sided translucent non-woven tape

tesa® 68618 is a translucent, double-sided self-adhesive tape consisting of a non-woven backing and a tackified acrylic adhesive.

tesa® 68618 features specially:

- High bonding strength on various kinds of foam, plastic and metal surfaces.
- Good temperature resistance
- Good converting properties

Main Application

- General purpose mounting application
- Lamination of foam and felt

Technical Data

Backing material non-woven

Adhesion to

 Steel (initial) ABS (initial) Aluminium (initial) PC (initial) PET (initial) PMMA (initial) PP (initial) PS (initial)	9.0 N/cm 6.5 N/cm 5.8 N/cm 8.8 N/cm 5.7 N/cm 9.7 N/cm 4.3 N/cm 7.7 N/cm	Steel (after 14 days) ABS (after 14 days) Aluminium (after 14 days) PC (after 14 days) PET (after 14 days) PMMA (after 14 days) PP (after 14 days) PS (after 14 days)	11.0 N/cm 10.0 N/cm 10.4 N/cm 9.1 N/cm 7.3 N/cm 10.1 N/cm 4.7 N/cm
PVC (initial)	5.4 N/cm	PVC (after 14 days)	10.6 N/cm

Properties

Tack
 Static shear resistance at 23°C

Evaluation across relevant tesa® assortment: •••• very good •• good •• medium • low

Additional Information

Liner variants:

PV43 white PE-coated paper liner / blue tesa logo

For latest information on this product please visit http://l.tesa.com/?ip=68618

tesa to work with