



Flexible, tearable and
waterproof

tesa® 4613 is an utility grade duct tape suitable for both indoor and outdoor applications. It comprises a natural-rubber adhesive mass and can be torn by hand. The duct tape is also suited to rough surfaces and is waterproof.

tesa® 4613 is used by professional vehicle painters for such tasks as fastening cables and trim panels as well as sticking components in place. Available in black, white and grey.

Duct tape - For the simple applications

Features

- Utility grade duct tape
- Good adhesion even on rough surfaces
- Water repellent
- Easy to tear by hand
- Very flexible due to low thickness

Main applications

- Sealing of ducts
- Fastening of protective films
- Sealing of rubbish bags
- Fixing, marking and packing

Technical properties

Elongation at break	18 %
Adhesive	Natural rubber
Total thickness	180µm
Temperature resistance (30min)	95°C
Tensile strength	30 N/cm
Backing material	PE laminated cloth
Adhesion to steel	4.3 N/cm
Mesh	27 count per square inch
Temperature resistance short term	80°C



Sealing of ducts



Fastening of cables



Fixing of cable on rough surfaces

tesa tape India Pvt. Ltd.
Phone: +91 22 4741 9215
tesa.com/en-in/company/locations

tesa.com

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All technical information and data above mentioned are provided to the best of our knowledge on the basis of our practical experience. They shall be considered as average values and are not appropriate for a specification. Therefore tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. The user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.