



tesa® Powerbond Double-Sided Mounting Pads Ultra Strong

Product Information

BNR 55790

Product Description

Each tesa® double-sided mounting pad can hold up to 6kg in weight. So put away the drill and get sticking instead.

Product Features

- Ideal for interior and exterior* use
- Ultra-strong hold
- Holds up to 6kg** per pad
- Holds on most smooth, sufficient firm surfaces

*Not UV-resistant. Protect from direct contact with water

**For flat objects up to 10mm thick

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- | | | | |
|--------------------|------------------|-------------------------------|---------|
| • Backing | PE foam | • Total thickness | 1100 µm |
| • Type of adhesive | synthetic rubber | • Holding power of tape up to | 6 KG/M |

Properties/Performance Values

- | | | | |
|--------------------------------|---|-----------------------------|---|
| • Ageing resistance (UV) | yes | • Humidity resistance | no |
| • Application temperature from | -10 °C | • Residue-free removability | no |
| • Applicationfield | Bedroom, Children's room, Hall, Home, Living room, Office, Garage, Garden, Bathroom | • Suitable surfaces | Even wood, Tiles, Most plastics, Glass, Acrylic glass, Steel, Metal |
| • Chemical Resistance | no | | |



tesa® Powerbond Double-Sided Mounting Pads Ultra Strong

Product Information

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.

For latest information on this product please visit <http://l.tesa.com/?cp=NaN>