



73522 FE-X (EA)



Product Information

Foam plate mounting tape: FLEX Product Design

Product Description

Double-sided foam tape

Product Features

- Foam properties: Low thickness tolerance. Long lasting, constant recovery characteristics.
- Adhesive properties: Low tack surface characteristics. Best plate bonding. Easy plate demounting. Excellent tape bonding towards sleeve side.
- Flexible PE reinforcement film to compensate for the expansion of thin-walled sleeves.

Application Fields

Mounting of 1,14 mm (0,045") and 1,70 mm (0,067") flexographic printing plates onto steel /alu /PU and glassine cylinders

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- | | | | |
|--------------------|------------------------------|-------------------|--------|
| • Backing | PE foam with film lamination | • Total thickness | 550 µm |
| • Type of adhesive | tackified acrylic | • Color | red |
| • Type of liner | PP | | |

Properties/Performance Values

- | | | | |
|-----------------|------|----------------------|-----|
| • Color of foam | red | • Thickness category | 500 |
| • Hardness | soft | | |

Additional Information

Available liner options:

- PV0: White embossed PP-liner
- PV21: Transparent structured easy application (EA) PET liner for excellent air removal during plate and tape mounting



73522 FE-X (EA)

Product Information

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=73522>