

# tesa® 4120 hand

# **Product Information**

#### General purpose parcel tape for packing and closing medium-weight shipping boxes

#### **Product Description**

tesa® 4120 is a packaging tape based on a PVC-film backing and a natural rubber adhesive.

tesa® 4120 can be used on manual and automatic sealing equipment.

## **Product Features**

- The natural rubber adhesive system offers very good adhesive properties to various surfaces and can be removed without leaving behind any residue.
- tesa<sup>®</sup> 4120 tape is ideal for manual sealing equipment, though it can also be used with an automatic sealing machine.
- The tape is convenient to use, and unwinds smoothly, steadily, and quietly.

## **Application Fields**

- Packaging and closing
- Sealing of medium-weight shipping boxes

#### Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

#### **Product Construction**

•	Backing	PVC film	•	Total thickness	49 µm
٠	Type of adhesive	natural rubber			
		1			

#### **Properties/Performance Values**

• E	longation at break	75 %	•	Manual application	yes
• T	ensile strength	43 N/cm	•	Packaging Weight	Up to 25 kg
• A	Automatic application	yes	٠	Silent unwinding	yes
•  -	land tearability	very good	٠	Suitable for deep freezing	yes

#### Adhesion to Values

Steel 2 N/cm



# tesa® 4120 hand

**Product Information** 

## **Additional Information**

tesa® 4120 is easily printable. Available colours: white, havana and transparent

#### Disclaimer

tesa<sup>®</sup> products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa<sup>®</sup> product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



Page 2 of 2 – as of 07/03/24 – en-NG