



# tesa<sup>®</sup> 4280 PV0



## Product Information

PVC Shipping tape with strong adhesive power

## Product Description

tesa<sup>®</sup> 4280 is a self-adhesive tape based on 25µm PP-film and a synthetic rubber adhesive. The product is available in 3 colours and has a noisy unwind.

## Application Fields

- Packaging, bundling and closing
- Sealing of light and medium-range weight cartons

## Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

## Product Construction

- |                    |                  |                   |       |
|--------------------|------------------|-------------------|-------|
| • Backing          | PP film          | • Total thickness | 42 µm |
| • Type of adhesive | synthetic rubber |                   |       |

## Properties/Performance Values

- |                       |         |                      |     |
|-----------------------|---------|----------------------|-----|
| • Elongation at break | 145 %   | • Manual application | yes |
| • Tensile strength    | 40 N/cm |                      |     |

## Adhesion to Values

- |         |          |
|---------|----------|
| • Steel | 4.8 N/cm |
|---------|----------|



# tesa<sup>®</sup> 4280 PV0

## Product Information

### Additional Information

Available colours: white, brown and transparent.

## Disclaimer

tesa<sup>®</sup> products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa<sup>®</sup> product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=04280>