



# tesa® Professional 4163 Standard Duct Tape

## Product Information

Multifunctional soft PVC insulating tape – ideal for electric installations

## Product Description

Our premium adhesive tape tesaflex® 4163 consists of soft PVC and is ideally suited for applications around electronics. As an insulating tape, it's used e.g. to mark cables, but because of its characteristics, it can also be used as a repairing tape. The special adhesive made from acrylate provides a high UV and temperature resistance. The professional insulation tape is therefore highly robust and can be used for up to 104 weeks outdoors. Furthermore, tesaflex® 4163 is also resistant to acids and solvents.

## Application Fields

- Electric installation work, e.g. insulating cable coating
- Isogeno-gray product variant for color matching in installation work, e.g. for heating pipes
- Splicing applications
- Also suitable for repairs, marking and bundling

## Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

## Product Construction

- |                    |          |                   |        |
|--------------------|----------|-------------------|--------|
| • Backing          | soft PVC | • Total thickness | 130 µm |
| • Type of adhesive | acrylic  |                   |        |

## Properties/Performance Values

- |                       |       |                    |         |
|-----------------------|-------|--------------------|---------|
| • Elongation at break | 250 % | • Tensile strength | 30 N/cm |
|-----------------------|-------|--------------------|---------|



# tesa® Professional 4163 Standard Duct Tape

## Product Information

### Additional Information

It conforms to US safety standard 302. The isogenogrey colour is suitable for installation of water pipes.

## Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=04163>