



tesa® Softprint 72129 Steelmaster TP



Product Information

Foam plate mounting tape: CLASSIC Product Design

Product Description

Double-sided foam tape

Foam properties

- Low thickness tolerance
- Long lasting, constant recovery characteristics

Adhesive properties

- Medium tack surface characteristics
- Sufficient plate bonding
- Easy plate demounting
- Sufficient tape bonding towards sleeve side

Additional property

- Structured PP-liner to prevent formation of air pockets when the plate is mounted

Application Fields

Mounting of 1,14 mm (0,045") and 1,70 mm (0,067") flexographic printing plates onto steel /alu /PU and glassine cylinders

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- | | | | |
|--------------------|------------------------------|-------------------|--------|
| • Backing | PE foam with film lamination | • Type of liner | PP |
| • Type of adhesive | tackified acrylic | • Total thickness | 550 µm |

Properties/Performance Values

- | | | | |
|-----------------|------------|----------------------|-----|
| • Color of logo | grey | • Thickness category | 500 |
| • Hardness | extra-hard | | |



tesa® Softprint 72129 Steelmaster TP

Product Information

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.

For latest information on this product please visit <http://l.tesa.com/?ip=72129>