



tesa® Softprint 52060 BigFoam



Product Information

Foam plate mounting tape for flexographic printing

Product Description

tesa® 52060 Softprint BigFoam is a 1500µm double-coated foam tape designed specifically for mounting photopolymer plates in wide-web film and paper flexographic printing.

Due to its medium hardness foam it is particularly suited for high quality combination of half-tone and solid work.

tesa® Softprint BigFoam offers the following benefits:

- tesa® Softprint BigFoam is highly compressible and therefore offers improved print quality and higher running speeds
- tesa® Softprint's BigFoam unique construction ensures that print quality is maintained even on extended print runs
- The special adhesive ensures simple mounting, easy repositioning, and demounting of plate and tape without residues
- During printing a very good bond of tape and plate is achieved. Plates stay securely in place with no edge lifting and no plate movement
- The structured PP-liner prevents the formation of air pockets when plate mounting

Application Fields

tesa® 52060 Softprint BigFoam is a 1500µm (60 mil) category double-coated foam tape, designed specifically for mounting photopolymer plates in wide-web film and paper flexographic printing.

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- | | | | |
|--------------------|-------------------|-----------------|----|
| • Backing | PE foam | • Type of liner | PP |
| • Type of adhesive | tackified acrylic | | |

Properties/Performance Values

- | | | | |
|------------|--------|----------------------|------|
| • Hardness | medium | • Thickness category | 1500 |
|------------|--------|----------------------|------|



tesa® Softprint 52060 BigFoam

Product Information

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.

For latest information on this product please visit <http://l.tesa.com/?ip=52060>