

# tesa® 60400

## **Product Information**



tesa® 60400 – Bio & Strong

## **Product Description**

tesa® 60400 is a bio-based packaging tape which is suitable for medium-weight packaging applications (15–30 kg). The backing material chosen for this tape is polylactide acid, also known as PLA. PLA is 100% made from renewable feedstocks such as corn starch, tapioca roots and sugarcane. The system adhesive used for this tape is a natural rubber with a natural-based resin. Thanks to the smart choice of raw materials and its outstanding design, tesa® 60400 is produced with a bio-carbon content of 98% and, consequently, a reduced carbon footprint.

#### Sustainability Features

- Total bio-based carbon content of 98%
- Official certification from DIN-CERTCO and TÜV AUSTRIA (highest possible rating)
- Lower carbon emissions compared to other standard packaging tapes
- · Solvent-free production process

#### **Technical Features**

- · Strong adhesion
- · Robust backing material
- · Excellent performance on recycled cardboards

#### One step forward

This marker is our attempt to help you determine more sustainable products more easily. Read more about it: https://www.tesa.com/product-sustainability

## Sustainable Aspects



For more information: https://www.tesa.com/product-sustainability

## **Application Fields**

- Sealing of medium-weight cardboard boxes (15–30 kg)
- · Suitable for manual and automatic dispensers
- · Packaging, bundling and closing



# tesa® 60400

# **Product Information**

## Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

#### **Product Construction**

•	Backing	Polylactide (PLA) •	Bio-based carbon	98 %
	Type of adhesive	natural rubbar	content of liner /acc ASTM	

Type of adhesive natural rubber content of liner (acc. ASTM D6866)

#### **Product Assortment**

Available colors transparent

# **Properties/Performance Values**

•	Elongation at break	185 %	•	Packaging Weight	Up to 25 kg
•	Tensile strength	30 N/cm	•	Silent unwinding	no
•	Automatic application	yes	•	Suitable for dangerous goods	no
•	Hand tearability	good	•	Suitable for deep freezing	yes
•	Manual application	yes			

## Adhesion to Values

• Steel 3.5 N/cm

## **Additional Information**

tesa® 60400 is printable with all types of ink systems

## Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.

