



tesapack® 58572

Product Information

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

• Backing	BOPP	• Total thickness	41 µm
• Type of adhesive	water-based acrylic		

Properties/Performance Values

• Tensile strength	38 N/cm	• Reusable	no
• Adhesive strength	Light adhesion	• Roll width max	50 mm
• Ageing resistance (UV)	yes	• Serrated blade	_NULL
• Applicationfield	Office, Home	• Solvent free	yes
• Batteries included	no	• Spare part service	no
• Batteries required	no	• Suitable surfaces	Cardboard
• Hand tearability	no	• Tear resistance	yes
• Low noise unwinding	no	• Tensibility	147 %
• Material	PP (polypropylene)	• Tension control	_NULL
• Max roll length	66 m	• Transparency	good
• Residue-free removability	no	• Writable	no

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=58572>