

tesa® 4263

Product Information



General Purpose BOPP Carton Sealing Tape With Natural Rubber

Product Description

tesa® 4263PV7 features a flexible 25 µm PP backing with a natural rubber adhesive. The natural rubber adhesive provides good tack, adhesion properties and environmental stability. It unwinds easily and is suitable for manual and automated application in manufacturing industry, food and beverages or e-commerce.

Product Features

- Flexible BOPP backing
- Tacky with good adhesion performance
- Suitable for application in cold environment down to 5°C
- Good environmental stability

Application Fields

- Sealing light weight cartons up to 15kg
- For manual and automated closing processes
- Applications where silent unwinding is not required

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- | | | | |
|--------------------|----------------|-------------------|-------|
| • Backing | PP film | • Total thickness | 43 µm |
| • Type of adhesive | natural rubber | | |

Properties/Performance Values

- | | | | |
|-------------------------|---------|-----------------------|-------------|
| • Elongation at break | 140 % | • Low unwinding force | yes |
| • Tensile strength | 35 N/cm | • Packaging Weight | Up to 15 kg |
| • Automatic application | yes | • Silent unwinding | no |

Adhesion to Values

- | | |
|---------|-----------|
| • Steel | 5.25 N/cm |
|---------|-----------|

tesa® 4263

Product Information

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=4263PV7>