

# tesa® 55964

## Product Information



Colored PVC packaging tape

### Product Description

tesa® 55964 is a packaging tape featuring a conformable, colored 35 micron PVC backing with a versatile natural rubber adhesive. It is ideal for sealing bags, small carton board boxes or metal cans as well as corrugated carton boxes.

### Product Features

- Excellent tack and adhesion properties
- Silent unwinding
- Resistant to temperature changes
- Good printability

### Application Fields

- Carton sealing
- Sealing metal tins and plastic bags
- Marking or color-coding due to availability of 4 colors

### Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

### Product Construction

• Backing	PVC film	• Total thickness	55 µm
• Type of adhesive	natural rubber		

### Product Assortment

• Available colors	blue, green, red, yellow
--------------------	--------------------------

### Properties/Performance Values

• Elongation at break	75 %	• Silent unwinding	yes
• Tensile strength	52 N/cm	• Transport Information	Temperature 0-70°C
• Hand tearability	good		

### Adhesion to Values

• Steel	1.6 N/cm
---------	----------

# tesa® 55964

## Product Information

### Storage Conditions

#### **Storage Conditions**

Store in original packaging protected from direct light and heat at 23°C and 50% relative humidity. The product retains its performance and properties for 12 months from date of delivery if stored under proper conditions.

### Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=55964>