

tesa® 55960

Product Information



General Purpose PVC Packaging Tape

Product Description

tesa® 55960 is a packaging tape based on a polyvinylchloride-film backing in combination with a natural rubber adhesive. A high tack and short dwell time ensure optimal security for your carton just shortly after the tape has been applied.

Product Features

- The natural rubber adhesive system offers very good adhesive properties to various surfaces
- The tape is convenient to use, and unwinds smoothly, steadily, and quietly.

Application Fields

- tesa® 55960 is used for the manual sealing of medium-range weight cartons
- Effortless and low-noise unwinding makes the tape ideal for convenient large-scale use in various industries
- A high tack and short dwell time ensure a fast and reliable hold

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

| | | | |
|--------------------|----------------|-------------------|-------|
| • Backing | PVC film | • Total thickness | 50 µm |
| • Type of adhesive | natural rubber | | |

Product Assortment

| | |
|--------------------|-------|
| • Available colors | white |
|--------------------|-------|

Properties/Performance Values

| | | | |
|-----------------------|---------|--------------------|-----|
| • Elongation at break | 75 % | • Hand tearability | yes |
| • Tensile strength | 50 N/cm | • Silent unwinding | yes |

Adhesion to Values

| | |
|---------|--------|
| • Steel | 2 N/cm |
|---------|--------|

tesa® 55960

Product Information

Additional Information

Tape application is best accomplished at room temperature. Once applied tesa® 55960 performs well throughout the normal temperature range in typical shipping and storage conditions.

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=55960WT>