

tesa® extra Power 56348

Product Information

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

• Backing	PE-film with PET-filament	• Total thickness	215 µm
• Type of adhesive	synthetic rubber		

Properties/Performance Values

• Tensile strength	46.3 N/cm	• Residue-free removability	no
• Adhesive strength	High adhesion	• Solvent free	yes
• Ageing resistance (UV)	yes	• Suitable surfaces	Even wood, Tiles, Most plastics, Glass, Metal
• Application temperature from	10 °C		
• Application temperature to	50 °C		
• Area of use	In- and Outdoor	• Tear resistance	yes
• Ecofriendly packaging	no	• Temperature resistance	yes
• Hand tearability	yes	• Tensibility	19 %
• Humidity resistance	yes	• UV resistant	yes
• Oil and grease resistance	yes	• Water resistance	yes
• Ozone resistance	yes	• Waterproof	yes
		• Writable	no

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=56388DIY>