

tesa® extra Power 56064

Product Information

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

• Backing	Silicone	• Total thickness	500 µm
-----------	----------	-------------------	--------

Properties/Performance Values

• Tensile strength	33 N/cm	• Residue-free removability	yes
• Adhesive strength	Very high adhesion	• Solvent free	yes
• Ageing resistance (UV)	yes	• Suitable surfaces	Even wood, Tiles, Brick, Most plastics, Glass, Acrylic glass, Plaster, Metal, Steel, Stone
• Application temperature from	-60 °C		
• Application temperature to	+260 °C		
• Area of use	Outdoor		
• Hand tearability	no	• Tear resistance	yes
• Humidity resistance	yes	• Temperature resistance	yes
• Oil and grease resistance	yes	• Tensibility	750 %
• Ozone resistance	yes	• UV resistant	yes
		• Water resistance	yes
		• Waterproof	yes
		• Writable	no

Certificates

Certified according to

UL 510

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=4600DIY>