

tesa[®] 4380

HT Paint Overspray Protection Film

Product Information

Large Area Masking for the Automotive Two-Tone Paint Process

Product Description

tesa[®] paint overspray protection film is a paintable and tear resistant translucent film for large area masking in the automotive paint process to prevent paint overspray. It prevents the base color painted area (body or roof) from overspray while applying the contrast color.

We offer our Overspray Protection Film as specific, tailor made tesa[®] RollMasker solutions in a variety of sizes to protect various types of vehicles.

- Easy to cut: Yes
- Demasking: After oven
- Robustness: Good

Product Features

- Durable film provides excellent paint overspray adhesion
- Reduces costs associated with removing overspray
- Temperature resistance up to 195°C (short term)
- Our non-sticky specially formulated high temperature film offers excellent paint adhesion and paint overspray adhesion.
- The film clings to vehicle which makes it easy to handle.
- It resists paint flaking and supports a fast and clean removal in one piece.
- Good tear resistance keep film intact during painting
- tesa[®] RollMasker is a two-in-one solution of a premium masking tape combined with our special protective film for sensitive, time saving large area masking.

Application Fields

Large Area Masking for the Automotive Two Tone Paint Process

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- | | | | |
|--------------------|------|-------------------|-------|
| • Type of adhesive | none | • Total thickness | 30 µm |
|--------------------|------|-------------------|-------|

Properties/Performance Values

- | | |
|--------------------|---------|
| • Tensile strength | 25 N/cm |
|--------------------|---------|

Additional Information

Available Sizes:

For latest information on this product please visit <http://l.tesa.com/?ip=4380PV3>

tesa[®] 4380

HT Paint Overspray Protection Film

Product Information

Additional Information

4380 HT RM Film 1500MX1520MM

4380 HT RM Film 1500MX1820MM

4380 HT RM Film 1500MX1620MM

4380 HT RM Film 1000MX2350MM

Disclaimer

tesa[®] products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa[®] product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=4380PV3>