

tesa®

Product Information



40595

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- | | | | |
|-----------------------|-------------------------|---------------|-----|
| • Type of adhesive | Silane modified polymer | • Splashproof | yes |
| • Holding power up to | 8 Kg | | |

Properties/Performance Values

- | | | | |
|-----------------------|------------------|-----------------------------|---|
| • Chemical Resistance | no | • Residue-free removability | yes |
| • Curing time | 12 hour(s) | • Reusable | yes |
| • Design series | tesa® MOON | • Reusable with | Adapter BK20 |
| • Dishwasher safe | no | • Shape of wall piece | Round |
| • Hazard material | yes | • Solvent free | yes |
| • Material | PVD coated metal | • Suitable surfaces | Glazed Tiles, Marble, Glass, Metal, Stone, Concrete, Even wood, Most plastics |
| • Number of arms | Two-armed | | |
| | | • UV resistant | yes |

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?cp=40595>