

tesa®

Product Information

56496, 56497

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

• Backing	PE film	• Total thickness	170 µm
• Type of adhesive	synthetic rubber		

Properties/Performance Values

• Tensile strength	35 N/cm	• Residue-free removability	no
• Abrasion resistance	yes	• Solvent free	yes
• Adhesive strength	Very high adhesion	• Suitable surfaces	Glass, Most plastics, Steel, Metal
• Ageing resistance (UV)	yes	• Tear resistance	yes
• Area of use	In- and Outdoor	• Temperature resistance	yes
• Hand tearability	yes	• UV resistant	yes
• Oil and grease resistance	yes	• Waterproof	yes
• Ozone resistance	yes	• Writable	no

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?cp=56496DIY>