



tesa[®] 7190

Product Information

High performance decorative film for Black Out Design and Permanent Protection of sensitive surfaces.

Product Description

The self adhesive tape consist of a black PVCfilm coated with a pure acrylic adhesive. tesa[®] 7190 can be applied for exterior and interior decorative purposes in the automotive industry.

The product features perfect optical appearance and long lasting adhesion properties. It can also be applied for the permanent protection of car parts from mechanical damage and to seal holes in the car body work. The film can be shaped when heated and can also be used on 3D-surfaces.

Application Fields

tesa[®] 7190 is designed for exterior and interior decorative application and permanent protection around the car body. This tape has a perfect visual appearance and long lasting adhesion properties on painted surfaces.

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- | | | | |
|--------------------|----------|-------------------|--------|
| • Backing material | PVC film | • Total thickness | 185 µm |
| • Type of adhesive | acrylic | | |

Properties/Performance Values

- | | |
|--------------------|---------|
| • Tensile strength | 60 N/cm |
|--------------------|---------|

Additional Information

The material can be delivered either in roll form or as die-cuts.

The special paper liner guarantees an accurate die-cutting process and perfect handling during application.



tesa[®] 7190

Product Information

Disclaimer

tesa[®] products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa[®] product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=07190>