




# tesa® 88008

## Product Information



## 200µm Optically Clear Adhesive for Automotive Applications

### Product Description

tesa® 880xx series OCA is acrylic adhesive with high transmittance. It is designed as PSA type for easy lamination of automotive parts. Its outgassing feature makes optical bonding free of bubbles. In addition, 880xx series shows outstanding yellowing resistance, which helps the final parts look good as new even after years.

### Product Features

- High transmission and low haze
- High bonding strength
- Superb outgassing performance
- Outstanding yellowing resistance
- Excellent temperature, humidity and UV resistance
- Excellent ITO compatibility (acid free)
- Smooth and easy liner removal

### Application Fields

tesa® 880xx OCA series is suitable for lamination between:

- Cover lens and display panel
- Glass and functional films
- Other optical laminations

### Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

### Product Construction

• Backing material	none	• Color	transparent
• Type of adhesive	acrylic	• Colour of liner	transparent
• Type of liner	PET	• Thickness of liner (easy release)	75 µm
• Total thickness	200 µm	• Thickness of liner (tight release)	100 µm

### Properties/Performance Values

• Ageing resistance (UV)	very good	• Refractive index	1.47
• Dielectric constant	6.7	• Release of liner - inside	tight
• Gap filling	5 %	• Release of liner - outside	easy
• Haze <	0.1 %	• Tack	medium
• Humidity resistance	very good	• Transmittance (380 - 780nm) >	99 %

For latest information on this product please visit <http://l.tesa.com/?ip=88008>



# tesa<sup>®</sup> 88008

## Product Information

### Adhesion to Values

- |                   |          |                |          |
|-------------------|----------|----------------|----------|
| • Glass (initial) | 7.6 N/cm | • PC (initial) | 7.1 N/cm |
|-------------------|----------|----------------|----------|

### Disclaimer

tesa<sup>®</sup> products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa<sup>®</sup> product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=88008>