



# tesa® 53315

## Product Information



Non-staining medium strength mono filament tape

### Product Description

tesa® 53315 is a medium strength polyester backed fiberglass reinforced filament tape.

tesa® 53315 has a high tack and good shear resistant adhesive system. It has very good aging properties and assures clean removal from many substrates. It is also non-staining.

### Application Fields

- Transport securing of appliances and office automation equipment
- Securing and stabilizing of furniture for transportation
- Securing of thin metal coils for end-tapping
- Bundling of medium weight goods, e.g. plastic pipes, flooring materials

### Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

### Product Construction

- |                    |                       |                   |        |
|--------------------|-----------------------|-------------------|--------|
| • Backing          | glassfibre / PET film | • Total thickness | 140 µm |
| • Type of adhesive | synthetic rubber      |                   |        |

### Properties/Performance Values

- |                    |          |                             |     |
|--------------------|----------|-----------------------------|-----|
| • Tensile strength | 380 N/cm | • Residue-free removability | yes |
|--------------------|----------|-----------------------------|-----|

### Adhesion to Values

- |         |        |
|---------|--------|
| • Steel | 7 N/cm |
|---------|--------|

### Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.

For latest information on this product please visit <http://l.tesa.com/?ip=53315>