



tesa[®] 58330

Product Information



55 µm s/s Black PET tape for Electrical Insulation applications

Product Description

tesa[®] 58330 is a black 55µm single sided PET tape with an acrylic adhesive that has been specifically designed for the electrical insulation of battery components.

Product Features

- High dielectric strength to ensure reliable electrical insulation
- Thin profile for applications with space constraints
- Low CO¹ footprint, no solvents
- Designed with a PET liner for automation
- Black color allows visual detection in production

1 2

Application Fields

- Electrical insulation of battery components of electric vehicles

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- | | | | |
|--------------------|----------|----------------------|-------------|
| • Backing | PET film | • Total thickness | 55 µm |
| • Type of adhesive | acrylic | • Color of liner | transparent |
| • Type of liner | PET film | • Thickness of liner | 30 µm |

Properties/Performance Values

- | | |
|-----------------------|------|
| • Elongation at break | 70 % |
|-----------------------|------|

Adhesion to Values

- | | | | |
|-----------------------|--------|---------|--------|
| • Aluminium (initial) | 6 N/cm | • Steel | 7 N/cm |
|-----------------------|--------|---------|--------|



tesa[®] 58330

Product Information

Disclaimer

tesa[®] products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa[®] product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=58330>