



# tesa<sup>®</sup> 4317

## Product Information



Finely crêped paper masking tape for paint spraying

### Product Description

The product is thin and flexible and, therefore, suitable for all general masking applications, as well as oven drying applications up to a temperature of 80 °C.

### Sustainable Aspects

55% bio-based content in total product excluding liner (by weight)



For more information: <https://www.tesa.com/product-sustainability>

### Product Features

- tesa<sup>®</sup> 4317 is resistant to wet sanding.
- The masking tape is suitable for a wide range of general masking applications without or with subsequent oven-drying up to a temperature of 80°C.
- The fine crepe paper backing is flexible and conformable and is easy to tear by hand.
- Paints and fillers adhere well to the reverse side, preventing any kind of flaking.

### Application Fields

The product is resistant to wet sanding. Paints and fillers adhere well to the backing.

The material can be used on painted metal, rubber, glass and chrome parts.

### Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

### Product Construction

- |                    |                       |  |        |
|--------------------|-----------------------|--|--------|
| • Backing          | slightly-creped paper | • Bio-based content of liner by weight (acc. EN 16785) | 55 %   |
| • Type of adhesive | natural rubber        | • Total thickness                                      | 140 µm |

### Properties/Performance Values

- |                       |         |                    |           |
|-----------------------|---------|--------------------|-----------|
| • Elongation at break | 10 %    | • Easy to remove   | yes       |
| • Tensile strength    | 38 N/cm | • Hand tearability | very good |

For latest information on this product please visit <http://l.tesa.com/?ip=04317>



# tesa<sup>®</sup> 4317

## Product Information

### Adhesion to Values

- Steel 3.3 N/cm

### Disclaimer

tesa<sup>®</sup> products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa<sup>®</sup> product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=04317>