



# tesa® Professional 4368

## Product Information

Masking film with slightly creped adhesive paper tape

### Product Description

Easy Cover® 4368 Universal is a combination of an environment-friendly HDPE film and a slightly creped adhesive paper tape for the masking of large areas in one working step. It is resistant against dispersion paints and can easily be removed after short term applications without residues.

Easy Cover 4368 is successfully tested for all standard indoor applications. It allows safe and precise fixation on even surfaces such as skirting boards, window sills, window and door frames. The embossed film avoids paint bleeding or leaking to the protected area. Easy Cover 4368 will achieve a clean paint result with straight paint edges.

### Application Fields

For base boards, window sills, door and window frames etc.

### Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

### Product Construction

- |                    |                       |                   |        |
|--------------------|-----------------------|-------------------|--------|
| • Backing          | slightly-creped paper | • Total thickness | 140 µm |
| • Type of adhesive | natural rubber        |                   |        |

### Properties/Performance Values

- |                       |         |                                |      |
|-----------------------|---------|--------------------------------|------|
| • Elongation at break | 10 %    | • Material of masking coverage | HDPE |
| • Tensile strength    | 38 N/cm |                                |      |

### Adhesion to Values

- |         |          |
|---------|----------|
| • Steel | 3.4 N/cm |
|---------|----------|



# tesa® Professional 4368

## Product Information

### Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=04368>