

## tesa® 51915

## **Product Information**



### Repulpable, Transfer Splicing Tape

### **Product Description**

tesa® 51915 is a very thin double-sided repulpable transfer tape consisting of a modified water soluble acrylic adhesive.

tesa® 51915 features especially

- · Very high tack properties
- · Very good adhesion values on coated and uncoated paper
- Very low splice thickness
- Good repulpability over full pH-range (pH3 –pH9)

Colour: Blue, Colourless

#### **Application Fields**

tesa® 51915 is particularly suitable for

- Flying splices in the paper producing and paper converting industry
- The use in hand dispensers or automatic applying processes
- Splicing of carbonless paper

### Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

#### **Product Construction**

•	Backing	none	•	Iotal thickness	50 μm
•	Type of adhesive	repulpable tackified	•	Color	blue
		acrylic			

Type of liner repulpable siliconised

paper

### **Properties/Performance Values**

Static shear resistance
medium
Tack
very good



# tesa® 51915

**Product Information** 

#### Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.

