



# tesa<sup>®</sup> 4258 Premium Grade PVC Duct Tape



## Product Information

Thick PVC duct tape with good impact and abrasion resistance

## Product Description

tesa<sup>®</sup> 4258 is a premium duct tape, comprised of a thick soft polyvinyl chloride (PVC) backing in combination with a rubber-based adhesive. The thick and highly conformable backing has a very good impact and abrasion resistance as well as good electrical insulation properties. tesa<sup>®</sup> 4258 has a soft, rubber-like and flexible consistency, even at low temperatures of -30°C. The tape is weatherproof and offers a good UV-stability. The rubber adhesive holds well on a wide variety of surfaces. tesa<sup>®</sup> 4258 is available in the colors silver and black.

### Benefits:

- Highly conformable and thick backing with good impact and abrasion resistance, even at low temperatures
- Good electrical insulation properties and UV-stability
- RoHS and REACH compliant
- Lead free

## Product Features

- The thick and highly conformable backing has a very good impact and abrasion resistance as well as good electrical insulation properties.
- tesa<sup>®</sup> 4258 has a soft, rubber-like and flexible consistency, even at low temperatures of -30°C. The tape is weatherproof and offers a good UV-stability.
- The rubber adhesive holds well on a wide variety of surfaces.
- Highly conformable and thick backing with good impact and abrasion resistance, even at low temperatures
- Good electrical insulation properties and UV-stability
- Flame retardant according to UL510 and DIN EN 60454-2 (VDE 0340-2):2008-05, clause 20
- RoHS and REACH compliant, lead free

## Application Fields

- tesa<sup>®</sup> 4258 is ideally used for joining poly-sheeting used in the building industry
- The thick PVC duct tape is suitable for applications such as joining and sealing flexible air-conditioning-ductwork
- tesa<sup>®</sup> 4258 can be used for sealing or pre-fabricated formwork

## Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

## Product Construction

- |                    |                |                   |        |
|--------------------|----------------|-------------------|--------|
| • Backing          | soft PVC       | • Total thickness | 150 µm |
| • Type of adhesive | natural rubber |                   |        |

For latest information on this product please visit <http://l.tesa.com/?ip=04258>



# tesa<sup>®</sup> 4258

## Premium Grade PVC Duct Tape

### Product Information

#### Properties/Performance Values

- |                       |         |                                |        |
|-----------------------|---------|--------------------------------|--------|
| • Elongation at break | 250 %   | • Dielectric breakdown voltage | 6000 V |
| • Tensile strength    | 35 N/cm | • Hand tearability             | good   |

#### Adhesion to Values

- |         |        |
|---------|--------|
| • Steel | 2 N/cm |
|---------|--------|

### Disclaimer

tesa<sup>®</sup> products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa<sup>®</sup> product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=04258>