



# 54804

## Black Line

### Product Information

Deep black acrylic foam tape

### Product Description

tesa® ACX<sup>plus</sup> 54804 is a deep black acrylic foam tape for exterior attachment parts.

The visco-elastic, medium density acrylic foam core of tesa® ACX<sup>plus</sup> 54804 optimally absorbs and dissipates dynamic and static loads. This exceptional capability enables tesa® ACX<sup>plus</sup> 54804 to compensate for extreme physical stress as caused by different thermal elongation of bonded parts in rapidly changing temperatures.

#### Features:

- \* Visco-elastic acrylic foam core to compensate for different thermal elongation of bonded parts
- \* Superior wetting even of rough surfaces to ensure a very high initial and ultimate adhesion
- \* Deep black colour for enhanced appearance and high design flexibility
- \* Closed cell acrylic foam core for reliable sealing to prevent water penetration
- \* High humidity and UV resistance

### Product Features

- Visco-elastic acrylic foam core to compensate for different thermal elongation of bonded parts
- Superior wetting even of rough surfaces to ensure a very high initial and ultimate adhesion
- Deep black colour for enhanced appearance and high design flexibility
- Closed cell acrylic foam core for reliable sealing to prevent water penetration
- High humidity and UV resistance
- The exceptional capability enables tesa® ACX<sup>plus</sup> 54804 to compensate for extreme physical stress as caused by different thermal elongation of bonded parts in rapidly changing temperatures.

### Application Fields

Permanent exterior mounting of

- \* Inlay mounting into door sill trim
- \* Emblems
- \* Decorative trims and body side moldings

For latest information on this product please visit <http://l.tesa.com/?ip=54804>



# 54804

## Black Line

### Product Information

#### Application Fields

\* Windscreen weather strips

\* Locator pins

### Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

#### Product Construction

• Backing	foamed acrylic	• Total thickness	400 µm
• Type of adhesive	tackified acrylic	• Color	deep black

#### Properties/Performance Values

• Ageing resistance (UV)	very good	• Humidity resistance	very good
--------------------------	-----------	-----------------------	-----------

#### Adhesion to Values

• Steel (initial)	12 N/cm	• Steel (after 3 days)	22 N/cm
-------------------	---------	------------------------	---------

### Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=54804>