

# tesa® Softprint 73524 FE-X, Medium

**Product Information** 

tesa Softprint FE-X EA

# **Product Description**

Double-sided foam tape

### Foam properties

- Low thickness tolerance
- Long lasting, constant recovery characteristics

#### Adhesive properties

- Low tack surface characteristics
- Best plate bonding
- Easy plate demounting
- Excellent tape bonding towards sleeve side

#### Addtional property

- Structured PP-liner to prevent formation of air pockets when the plate is mounted
- Flexible PE reinforcement film to compensate for the expansion of thin-walled sleeves

# **Application Fields**

Mounting of 1,14 mm (0,045") and 1,70 mm (0,067") flexographic printing plates onto steel /alu /PU and glassine cylinders.

## Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

## **Product Construction**

<ul><li>Backing</li><li>Type of adhesive</li></ul>	PE foam with film lamination tackified acrylic	•	Type of liner Total thickness	ΡΡ 550 μm
Properties/Performance Values				
<ul><li>Color of foam</li><li>Hardness</li></ul>	purple medium	٠	Thickness category	500





# tesa® Softprint 73524 FE-X, Medium

**Product Information** 

## Disclaimer

tesa<sup>®</sup> products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa<sup>®</sup> product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



Page 2 of 2 – as of 14/12/24 – en-SG