

# tesa® 51300

# **Product Information**



#### Heat-resistant universal bandoliering tape

# **Product Description**

This tape consists of a crêped paper with a heat-resistant thermosetting adhesive.

For short term exposure, the maximum applicable temperature is 180 °C.

# **Application Fields**

The product is therefore particularly suitable for bandoliering of components which, as part of the production process, have to pass through a drying zone after lacquering, or are exposed to artificial ageing by heat.

Due to the age-resistant adhesive, tesa® 51300 is especially suitable for stock-belting.

# Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

#### **Product Construction**

<ul> <li>Backing slightly-creped paper</li> <li>Total thickness</li> </ul>	165 µm
--	--------

Type of adhesive natural rubber

#### **Properties/Performance Values**

Elongation at break
 12 %
 Tensile strength
 42 N/cm

#### Adhesion to Values

• Steel 4.1 N/cm



# tesa® 51300

**Product Information** 

#### **Additional Information**

Colours: chamois, blue

#### Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.