



tesa® 4120

hand

Product Information

General purpose carton sealing tape

Product Description

tesa® 4120 is a packaging tape based on a PVC-film backing and a natural rubber adhesive.

tesa® 4120 can be used on manual and automatic sealing equipment.

Product Features

- The natural rubber adhesive system offers very good adhesive properties to various surfaces and can be removed without leaving behind any residue.
- tesa® 4120 tape is ideal for manual sealing equipment, though it can also be used with an automatic sealing machine.
- The tape is convenient to use, and unwinds smoothly, steadily, and quietly.

Application Fields

tesa® 4120 is used for manual sealing of cartons of medium-range weight.

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- | | | | |
|--------------------|----------------|-------------------|-------|
| • Backing | PVC film | • Total thickness | 49 µm |
| • Type of adhesive | natural rubber | | |

Properties/Performance Values

- | | | | |
|-------------------------|-----------|------------------------------|-------------|
| • Elongation at break | 75 % | • Manual application | yes |
| • Tensile strength | 43 N/cm | • Packaging Weight | Up to 25 kg |
| • Automatic application | yes | • Silent unwinding | yes |
| • Hand tearability | very good | • Suitable for deep freezing | yes |

Adhesion to Values

- | | |
|---------|--------|
| • Steel | 2 N/cm |
|---------|--------|



tesa® 4120 hand

Product Information

Additional Information

tesa® 4120 is easily printable. Available colours: white, havana and transparent

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=04120>