

# 52018 Steel Master

#### **Product Information**

Foam plate mounting tape (extra soft) for printing screens

## **Product Description**

tesa $^{\circ}$  52018 Softprint X-Soft 380  $\mu$ m is a double-coated foam tape, designed specifically for mounting photopolymer plates with a thickness of 1.14 mm (0.045") or 1.70 mm (0.067") in flexographic label printing.

The unique properties of tesa® 52018 Softprint X-Soft 380  $\mu$ m make it the ideal choice for finest screen print, especially where harder digital plates are in use. Additionally, the extra cushion allows faster printing speeds, whilst reducing the effects of unwanted press "bounce" and keeping plates down even on smaller diameter cylinders.

#### Foam properties

- · The extra soft foam is the ideal plate mounting solution in combination with harder, digital plates (for finest screen print)
- · Highly compressible foam, with superior recovery behavior for excellent print quality
- · Long lasting recovery characteristic for extended and high speed print runs
- · Low thickness tolerances for quick print preparation and reduced waste

#### Adhesive properties

- · Secure bonding to sleeve / cylinder, with specially enhanced removal properties
- · Optimal bonding to plate to avoid edge lifting or plate movement, with residue-free removal

#### Additional properties

- · The structured PP-liner prevents the formation of air pockets when plate mounting
- Yellow color coding of logo on backing indicates extra soft foam category

#### **Product Features**

- · Highly compressible foam, with superior recovery behavior for excellent print quality
- · Long lasting recovery characteristic for extended and high speed print runs
- · Low thickness tolerances for quick print preparation and reduced waste
- High bonding on open side to steel cylinder or sleeve to avoid plate movement
- High bonding to plate to avoid edge lifting or plate movement
- · Non increasing bonding power for easy repositioning and especially for easy demounting of plate and tape
- Very cohesive adhesive structure for demounting without adhesive residues
- The structured PP-liner prevents the formation of air pockets when plate mounting
- · Yellow color marking indicates the hard foam

#### **Application Fields**

tesa® 52018 Softprint x-Soft is a 380 $\mu$ m (15mil) category double-coated foam tape, designed spedifically for mounting photopolymer plates with a thickness of 1.14mm (0.045") or 1.70mm (0.067") in flexographic label printing.

#### Technical Information (average values)

The values in this section should be considered representative or typical only and should not be





# 52018 Steel Master

### **Product Information**

Technical Information (average values)

used for specification purposes.

#### **Product Construction**

<ul> <li>Backing</li> </ul>	PE foam with film	<ul> <li>Type of liner</li> </ul>	PP
	lamination	<ul> <li>Total thickness</li> </ul>	430 μm
<ul> <li>Type of adhesive</li> </ul>	tackified acrylic		

#### **Properties/Performance Values**

•	Color of logo	yellow	•	Thickness category	380
•	Hardness	extra soft			

### Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.

