



tesa[®] 51324

Product Information



tesa[®] 4324 as SAF

Product Description

tesa[®] 51324 is a finely crêped and wet resistant paper masking tape with a good flexibility and a high tensile strength.

Product Features

- Very high conformability for excellent bonding to rough and irregular surfaces
- Strong natural rubber
- adhesive for good bandoliering performance

Application Fields

tesa[®] 4324 is suitable for masking during paint spraying with oven drying (up to 80 °C).

Further applications are e.g.:

- bandoliering of yarn beams
- splicing of photo papers and veneers
- coil bandages

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- | | | | |
|--------------------|-----------------------|-------------------|--------|
| • Backing | slightly-creped paper | • Total thickness | 280 µm |
| • Type of adhesive | natural rubber | | |

Properties/Performance Values

- | | | | |
|-----------------------|------|--------------------|---------|
| • Elongation at break | 17 % | • Tensile strength | 47 N/cm |
|-----------------------|------|--------------------|---------|

Adhesion to Values

- | | |
|---------|--------|
| • Steel | 4 N/cm |
|---------|--------|



tesa[®] 51324

Product Information

Additional Information

The flexibility and the soft adhesive allow good adhesion to rough surfaces or complicated shapes and contours.

Disclaimer

tesa[®] products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa[®] product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=51324>