



# tesa® 61124

## Product Information



High temperature resistant polyester tape

### Product Description

tesa® 61124 is a premium polyester tape with a high temperature resistant silicone adhesive. The excellent temperature resistance makes it suitable for high demanding applications such as masking during powder coating, autoclave bonding operations during composite production or wave soldering processes. tesa® 61124 blue color provides an excellent visibility of the tape at first sight and makes it suitable for automatic detection. The masking tape's silicone adhesive system makes the tape extremely heat-resistant, withstanding extreme temperatures of up to 220°C for as long as 7 hours at a time. The high-temperature tape features easy application and easy one-piece removal without leaving residues behind.

Benefits:

- Long-term high temperature resistance (220°C / 7h or 200°C / 24h)
- Removable in one piece without leaving residues
- Excellent visibility and contrast

### Product Features

- Long-term high temperature resistance (220°C / 7h or 200°C / 24h)
- Removable in one piece without leaving residues
- Excellent visibility and contrast
- The high-temperature tape features easy application and easy one-piece removal without leaving residues behind.

### Application Fields

- tesa® 61124 is used for masking off areas that are to be protected during powder-coating processes and require a tape with excellent visibility and contrast
- The high-temperature tape is recommended for bonding and splicing of non-polar material, high temperature exposure and bonding operations during composite production
- tesa® 61124 can withstand temperatures of up to 220°C for 7 hours
- The masking tape features residue-free removal

### Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

### Product Construction

- |                    |          |                   |       |
|--------------------|----------|-------------------|-------|
| • Backing          | PETP     | • Total thickness | 60 µm |
| • Type of adhesive | silicone |                   |       |

For latest information on this product please visit <http://l.tesa.com/?ip=61124>



# tesa<sup>®</sup> 61124

## Product Information

### Properties/Performance Values

- Elongation at break 130 %
- Tensile strength 45 N/cm

### Adhesion to Values

- Steel 3.5 N/cm

## Disclaimer

tesa<sup>®</sup> products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa<sup>®</sup> product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=61124>