



tesa® Softprint 72526 FE-X (EA), Medium-Hard

Product Information

Foam plate mounting tape: CLASSIC product design



Product Description

Double-sided foam tape

Foam properties

- * Low thickness tolerance
- * Long lasting, constant recovery characteristics

Adhesive properties

- * Low tack surface characteristics
- * Best plate bonding
- * Easy plate demounting
- * Excellent tape bonding towards sleeve side

Additional property

- * Structured PP-liner to prevent formation of air pockets when the plate is mounted

Application Fields

Mounting of 1,14 mm (0,045") and 1,70 mm (0,067") flexographic printing plates onto steel /alu /PU and glassine cylinders



tesa® Softprint 72526 FE-X (EA), Medium-Hard

Product Information

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

• Backing	PE foam with film lamination	• Total thickness	550 µm
• Type of adhesive	tackified acrylic	• Color	white
• Type of liner	PP		

Properties/Performance Values

• Color of foam	white	• Hardness	medium-hard
• Color of logo	blue	• Thickness category	500

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=72526>