



tesa® 53949 PV2 matt gaffer tape



Product Information

Non-reflective polyethylene coated high grade cloth tape

Product Description

tesa® 53949 PV2 is a matt gaffer tape specially designed for the arts and entertainment industry. It consists of a PE coated 80 mesh woven PET fabric backing coated with a pressure sensitive natural rubber adhesive.

tesa® 53949 PV2 is the ideal solution for a wide range of applications whenever a non-reflective surface is important.

Features:

- light-absorbing, non-reflective
- good adhesion, even on rough surfaces
- abrasion resistant
- water repellent
- conformable
- easy to remove
- available in matt black, matt white, and matt silver

Application Fields

- On-stage/back-stage jobs in theatre, opera, cinema and music halls
- Fixing of cables on carpets, walls etc.
- Covering of shiny and glossy surfaces
- Fixing of cable links
- Sealing of joints
- Floor marking and fixing

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- | | | | |
|--------------------|-------------------|---------------------|----------|
| • Backing | PE extruded cloth | • Total thickness | 310 µm |
| • Type of adhesive | natural rubber | • Thickness of tape | _NULL µm |

Properties/Performance Values

- | | | | |
|-------------------------------|---------|--|--------------------------|
| • Elongation at break | 14 % | • Mesh | 80 count per square inch |
| • Tensile strength | 85 N/cm | • Straight tear edge | good |
| • Abrasion resistance | good | • Temperature resistance | 125 °C |
| • Backing appearance (visual) | matt | (removability from aluminum after 30 min exposure) | |
| • Hand tearability | good | • Water resistance | good |

For latest information on this product please visit <http://l.tesa.com/?ip=53949>



tesa[®] 53949

PV2 matt gaffer tape

Product Information

Adhesion to Values

- Steel 1.6 N/cm

Additional Information

Recommendation: please conduct a test on the application surface before using the product.

Complies with LV 312-1 Dielectric strength.

Disclaimer

tesa[®] products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa[®] product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.

For latest information on this product please visit <http://l.tesa.com/?ip=53949>