

tesa® 53949 PV2 matt gaffer tape

Product Information

Non-reflective polyethylene coated high grade cloth tape

Product Description

tesa® 53949 PV2 is a matt gaffer tape specially designed for the arts and entertainment industry. It consists of a PE coated 80 mesh woven PET fabric backing coated with a pressure sensitive natural rubber adhesive. tesa® 53949 PV2 is the ideal solution for a wide range of applications whenever a non-reflective surface is important.

Features:

- · light-absorbing, non-reflective
- · good adhesion, even on rough surfaces
- · abrasion resistant
- · water repellent
- · conformable
- · easy to remove
- · available in matt black, matt white, and matt silver

Application Fields

- · On-stage/back-stage jobs in theatre, opera, cinema and music halls
- Fixing of cables on carpets, walls etc.
- · Covering of shiny and glossy surfaces
- · Fixing of cable links
- · Sealing of joints
- · Floor marking and fixing

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

•	Backing	PE extruded cloth	•	Total thickness	310 µm
•	Type of adhesive	natural rubber	•	Thickness of tape	_NULL μm

Properties/Performance Values

 Elongation at break Tensile strength	14 % 85 N/cm	• Mesh	80 count per square inch
Abrasion resistance	good	 Straight tear edge 	good
Backing appearance (visual)Hand tearability	matt good	 Temperature resistance (removability from aluminum after 30 min exposure) 	125 ℃
		Water resistance	good



tesa® 53949 PV2 matt gaffer tape

Product Information

Adhesion to Values

• Steel 1.6 N/cm

Additional Information

Recommendation: please conduct a test on the application surface before using the product.

Complies with LV 312-1 Dialectric strength.

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.

