



tesa® 62019

Product Information

Card Labels

Product Description

tesa® 62019 consists of a double-sided polyester film with a pressure-sensitive, acrylic-based adhesive. One side of the label is made of a permanent adhesive that ensures a secure bond to paper. The other side is made of a non-permanent pressure-sensitive adhesive for the secure attachment of plastic cards. UV-fluorescent pigments make sensoric detection possible.

Features:

- Easily removable without leaving residues or damaging the card
- High adhesive reliability to all card surfaces and materials
- High processing reliability
- UV pigments enable the sensory label detection

Product Features

- Easily removable without leaving residues or damaging the card
- High adhesive reliability to all card surfaces and materials
- High processing reliability
- UV pigments enable the sensory label detection

Application Fields

Mailing of cards

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

• Backing	PETP	• Total thickness	120 µm
• Type of adhesive	modified acrylic	• Color	transparent with UV-particles
• Type of liner	glassine		

Properties/Performance Values

• Residue-free removability	yes
-----------------------------	-----

Adhesion to Values

• Steel (permanent side)	4 N/cm	• Steel (removable side)	0.3 N/cm
--------------------------	--------	--------------------------	----------

For latest information on this product please visit <http://l.tesa.com/?ip=62019>



tesa[®] 62019

Product Information

Additional Information

Standard version is PV3.

Label format: 38mm x 13mm

Labels/roll: 5000 pcs.

Disclaimer

tesa[®] products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa[®] product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=62019>