



54808 Black Line

Product Information

Precision Die Cut of 6808 ACX^{plus} Black Line 800µm

Product Description

tesa[®] 54808 is a die cut of ACX^{plus} 6808. It is a deep black acrylic foam tape for exterior attachment parts. The visco-elastic, medium density acrylic foam core of tesa[®] ACX^{plus} 6808 optimally absorbs and dissipates dynamic and static loads. This exceptional capability enables tesa[®] ACX^{plus} 6808 to compensate for extreme physical stress as caused by different thermal elongation of bonded parts in rapidly changing temperatures.

Features:

- Visco-elastic acrylic foam core to compensate for different thermal elongation of bonded parts
- Superior wetting even of rough surfaces to ensure a very high initial and ultimate adhesion
- Deep black colour for enhanced appearance and high design flexibility
- Closed cell acrylic foam core for reliable sealing to prevent water penetration
- High humidity and UV resistance

Product Features

- Visco-elastic acrylic foam core to compensate for different thermal elongation of bonded parts
- Superior wetting even of rough surfaces to ensure a very high initial and ultimate adhesion
- Deep black colour for enhanced appearance and high design flexibility
- Closed cell acrylic foam core for reliable sealing to prevent water penetration
- High humidity and UV resistance

Application Fields

Permanent exterior mounting of

- Emblems
- Decorative trims and body side moldings
- Spoilers
- Antennas
- Pillar appliques

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- | | | | |
|--------------------|-------------------|-------------------|------------|
| • Backing | foamed acrylic | • Total thickness | 800 µm |
| • Type of adhesive | tackified acrylic | • Color | deep black |

For latest information on this product please visit <http://l.tesa.com/?ip=54808>



54808

Black Line

Product Information

Properties/Performance Values

- Ageing resistance (UV) very good
- Humidity resistance very good

Adhesion to Values

- Steel (initial) 18 N/cm
- Steel (after 3 days) 30 N/cm

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=54808>