



# tesa<sup>®</sup> 51408

## Product Information



Flame retardant polyimide high grade masking tape

### Product Description

tesa<sup>®</sup> 51408 is a high temperature resistant masking tape featuring a polyimide backing with a silicone adhesive. Features and benefits include:

- Flame retardant
- Chemical resistance
- High temperature resistance (up to 260°C in continuous and up to 315°C in short term, intermittent usage)

### Product Features

- High temperature resistance (up to 260°C)
- Flame retardant according to UL510 and DIN EN 60454-2 (VDE 0340-2):2008-05, clause 20
- High chemical resistance and dielectric strength
- Residue-free removability for masking applications

### Application Fields

- Wave soldering
- Powder coating
- Chemical production processes

### Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

### Product Construction

- |                    |           |                   |       |
|--------------------|-----------|-------------------|-------|
| • Backing          | Polyimide | • Total thickness | 65 µm |
| • Type of adhesive | silicone  |                   |       |

### Properties/Performance Values

- |                       |         |                                |        |
|-----------------------|---------|--------------------------------|--------|
| • Elongation at break | 70 %    | • Dielectric breakdown voltage | 6000 V |
| • Tensile strength    | 46 N/cm | • Insulation class             | H      |

### Adhesion to Values

- |         |          |
|---------|----------|
| • Steel | 2.8 N/cm |
|---------|----------|



# tesa<sup>®</sup> 51408

## Product Information

### Disclaimer

tesa<sup>®</sup> products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa<sup>®</sup> product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=51408>