



# tesa<sup>®</sup> 68441

## Product Information

Transparent double-sided self-adhesive tape

### Product Description

tesa<sup>®</sup> 68441 is a transparent, double-sided self-adhesive tape consisting of a thin, conformable PET film backing and a tackified acrylic adhesive in differential design.

tesa<sup>®</sup> 68441 features esp.

- \* Outstanding adhesion level relative to low thickness
- \* Differential design for critical applications
- \* Excellent resistance to demanding environmental conditions
- \* Excellent conformability and adjustment to curved surfaces

### Product Features

- Outstanding adhesion level relative to low thickness
- Differential design for critical applications
- Excellent resistance to demanding environmental conditions
- Excellent conformability and adjustment to curved surfaces

### Application Fields

- Mounting of heat spreading parts
- Lamination in NFC antenna
- Very small design gap filling

### Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

### Product Construction

- |                    |                   |                   |             |
|--------------------|-------------------|-------------------|-------------|
| • Backing          | PET film          | • Total thickness | 10 µm       |
| • Type of adhesive | tackified acrylic | • Color           | transparent |



# tesa<sup>®</sup> 68441

## Product Information

### Properties/Performance Values

- |                                   |           |                                     |        |
|-----------------------------------|-----------|-------------------------------------|--------|
| • Ageing resistance (UV)          | very good | • Tack                              | low    |
| • Humidity resistance             | very good | • Temperature resistance long term  | 100 °C |
| • Static shear resistance at 23°C | good      | • Temperature resistance short term | 150 °C |
| • Static shear resistance at 40°C | good      |                                     |        |

### Adhesion to Values

- Steel (easy-side, initial) 5.5 N/cm

### Additional Information

Adhesion to Steel (easy-side, initial, ASTM D3330): 4.5N/cm

Adhesion to Steel (tight-side, initial, ASTM D3330): 5.8N/cm

Liner variants:

PV55 double PET liner (36µm transparent liner / 50µm blue liner)

### Disclaimer

tesa<sup>®</sup> products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa<sup>®</sup> product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=68441>