



tesa® 60650

Product Information



Universal aluminum tape

Product Description

tesa® 60650 is a universal aluminum tape based on a 50 µm (2 mil) aluminum foil and a transparent acrylic adhesive

Features:

- * Mechanical stable and conformable
- * Easy to unwind
- * Suitable for permanent applications
- * Barrier against moisture, gases and vapors
- * Electrically and thermally conductive
- * Aging resistant
- * Heat and light reflective
- * Flame retardant according to DIN 4102, class B1
- * Flame retardant according to the requirements in UL 510A

Application Fields

- Mounting of refrigerator coils in appliance industry
- * Joining and sealing of thermal insulation, ducts and pipes
- * To make substrates electrically and thermally conductive
- * To reflect heat radiation



tesa[®] 60650

Product Information

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

• Backing	aluminium foil	• Type of liner	none
• Type of adhesive	acrylic	• Total thickness	90 µm

Properties/Performance Values

• Elongation at break	6 %	• Hand tearability	very good
• Tensile strength	40 N/cm	• Operation temperature from	-40 °C
• Backing appearance (visual)	reflective	• Operation temperature up to	160 °C
• Easy to remove	no		

Adhesion to Values

• Backing	0.5 N/cm	• PVC (initial)	6 N/cm
• Glass (initial)	9 N/cm	• Steel	9 N/cm
• PE (initial)	4.5 N/cm		

Disclaimer

tesa[®] products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa[®] product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.