

# tesa® CaRes 51444 PV11

**Product Information** 

Repulpable, single-sided splicing tape

#### **Product Description**

tesa CaRes<sup>®</sup> 51444 is a single-sided repulpable splicing tape, with a liner consisting of a flat-back paper and a modified water soluble acrylic adhesive.

tesa CaRes® 51444 special features:

- The patented calcium resistant adhesive (CaRes) for a maximised life time of permanent splices on papers containing calcium carbonate (CaCO3)
- Very thin but strong backing to allow an especially low total splice thickness
- Printable and coatable backing for easy further processing
- Very high shear strength
- Very high heat resistance
- Very good adhesion values on most paper grades

tesa CaRes® 51444 is certified by independent laboratories for:

• Repulpability according to TAPPI UM-213 over full pH-range (pH3 – pH9)

### **Application Fields**

tesa<sup>®</sup> 51444 is particularly suitable for:

- Manual permanent butt splicing
- Use in automatic butt-splice applicators
- Security tape

#### Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

#### **Product Construction**

<ul><li>Backing</li><li>Type of adhesive</li><li>Type of liner</li></ul>	flat paper repulpable tackified acrylic repulpable siliconised paper	<ul><li>Total thickness</li><li>Color</li></ul>	50 μm blue
Properties/Performance Values			
<ul><li>Elongation at break</li><li>Static shear resistance</li></ul>	6 % very good	<ul><li>Tack</li><li>Tensile strength (crosswise)</li></ul>	medium 10 N/cm





# tesa® CaRes 51444 PV11

**Product Information** 

#### **Additional Information**

Other products for butt-splicing:

- tesa® 51445 stronger backing for higher splice security
- tesa® 51455 slit liner for easier manual splice application
- tesa® 51465 slit liner and splitting strip for secure tape fixation during the manual splice preparation
- tesa® 61445 black backing for optical detection

#### Disclaimer

tesa<sup>®</sup> products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa<sup>®</sup> product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.