



# tesa<sup>®</sup> 60372

## Product Information

50µm double sided black electrically conductive non-woven tape

### Product Description

tesa<sup>®</sup> 60372 is a black double sided electrically conductive self adhesive tape. It consists of an electrically conductive non-woven backing and an electrically conductive acrylic adhesive.

tesa<sup>®</sup> 60372 features especially:

- \* Enhanced electrical conductivity in XYZ-direction
- \* Highly reliable and stable conductivity even after damp heat conditions
- \* Good bonding strength
- \* Great conformability and adjustment to uneven surfaces
- \* Excellent grounding performance at small bonding area
- \* Black color

### Product Features

- Enhanced electrical conductivity in XYZ-direction
- Highly reliable and stable conductivity even after damp heat conditions
- Good bonding strength
- Great conformability and adjustment to uneven surfaces
- Excellent grounding performance at small bonding area

### Application Fields

- EMC applications
- \* Main board, FPC grounding
- \* Antenna grounding
- \* Electrostatic discharge applications

### Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

For latest information on this product please visit <http://l.tesa.com/?ip=60372>



# tesa<sup>®</sup> 60372

## Product Information

### Product Construction

• Backing	conductive non-woven	• Color	black
• Type of adhesive	conductive acrylic	• Color of liner	transparent
• Type of liner	PET	• Thickness of liner	50 µm
• Total thickness	50 µm		

### Properties/Performance Values

• Contact resistance z-direction (initial)	0.01 Ohm / square inch	• Surface resistance x-y-direction (adhesive)	0.1 Ohm / square
• Release of liner	easy	• Temperature resistance short term	200 °C
• Static shear resistance at 40°C	very good		

### Adhesion to Values

• Steel (after 14 days)	5.6 N/cm
-------------------------	----------

## Disclaimer

tesa<sup>®</sup> products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa<sup>®</sup> product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=60372>