


tesa[®] 7905

Product Information



5µm single sided matte black filmic tape

Product Description

tesa[®] 7905 is a matte black single sided tape consisting of an ultra-thin PET film backing and tackified acrylic adhesive.

Special features:

- * Thickness: 5µm
- * Strong & reliable bonding force
- * Refined matte black color tone
- * Low gloss level of 2.9 %
- * Excellent anti-fingerprint performance
- * Excellent solvent-resistance
- * Good light blocking

Application Fields

- Graphite sheet protection
- * Magnetic sheet protection
- * Ultrathin covering on various components in smartphone and tablet

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- | | | | |
|--------------------|----------|----------------------|-------|
| • Backing | PET film | • Total thickness | 5 µm |
| • Type of adhesive | acrylic | • Thickness of liner | 50 µm |
| • Type of liner | PET | | |

tesa[®] 7905

Product Information

Properties/Performance Values

- | | | | |
|--------------------------------|--------|-------------------------------------|--------|
| • Elongation at break | 10 % | • Optical density | 1.2 |
| • Tensile strength | 4 N/cm | • Temperature resistance short term | 140 °C |
| • Dielectric breakdown voltage | 700 V | | |

Adhesion to Values

- | | | | |
|------------------------|----------|-------------------------|----------|
| • ASTM (initial) | 0.9 N/cm | • Glass (after 14 days) | 1 N/cm |
| • ASTM (after 14 days) | 1 N/cm | • PC (initial) | 0.9 N/cm |
| • Glass (initial) | 1 N/cm | • PC (after 14 days) | 1.4 N/cm |

Disclaimer

tesa[®] products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa[®] product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=7905>